



CONTAINER

DESCRIPTION OF OFFERED MODULAR UNITS/ELEMENTS OF UNITS

For special elements or additional information about standard elements, do not hesitate to contact us and we will be glad to help you.

A. Description of subject A from the offer

Modular unit with external dimensions (LxWxH) 2,989 x 2,435 x 2,591 m, internal height is approx. 2,326 m. Unit is delivered as trans-pack.

Description	COLOUR	Num.	EM
FRAME OF UNIT (STRUCTURE, FLOOR, CEILING)			
- Painting of frame with dimension 2435x2989mm, painted in C3M 5 till 15 years, ISO12944-2	RAL 9002	1	PCS
- Trans-pack for loading horizontally on truck trailer		1	SET
- Floor frame of dimensions 2435x2989mm, H=120mm		1	PCS
- Eorklift pockets 250/90 mm on distance 1200 mm		1	PCS
- PVC floor covering in thickness of 1,5 mm, for floor of dimensions 2435x2989mm	grey	1	PCS
- Main floor plate made of water-repellent chipboard in thickness of 20mm, for floor of dim. 2435x2989mm		1	PCS
- Insulation for floor of dim. 2435x2989mm, DF 39, thickness 100mm, U=0,35W/m2K		1	PCS
- Ceiling frame of dimensions 2435x2989mm, H=200mm		1	PCS
- Internal wainscot of ceiling is made of chipboard of thickness 10mm, for ceiling of dim. 2435x2989mm		1	PCS
- Insulation of ceiling of dim. 2435x2989mm, DF 39, thickness 100 mm, U=0,36 W/m2K		1	PCS
- Pillars 210x152, S=3mm, L=2271mm, S350GD+Z140, for internal height 2,326 m		1	SET
FACADE PANELS			
- Facade panel FTVL 100, L=2290mm, DF 39, U=0,36W/m2K		8	PCS
- Facade panel FTVL 100-half, L=2290mm, DF 39, U=0,36W/m2K		2	PCS
WINDOWS AND GLAZINGS			
- Single folded PVC window with PVC roller shutter, D/K, dim. 885x1372mm, Uw=1,6 W/m2K		1	PCS
- Window frame for window 885 x 1372/1226 mm for wall of thickness 100-130 mm		1	PCS
DOORS			
- Doors EPS+AL single fold 905x2060mm, for wall thickness 60-90mm	RAL 9002	1	PCS
- Single folded doors are equipped with wider door jamb for thicker facade panels (100-130 mm)		1	PCS
- Aluminium ventilation grid of dim. 140x220 mm is installed into door wing, with possibility of hand regulation		1	PCS
ELECTRIC INSTALLATIONS			
- Electric fuse box with doors (flush-mounted), 12 places, IP 30 protection, suitable for dry rooms, NO system		1	PCS
- Connections (plug + socket) to the external electric system, PCE-32A/230V 4P (NO)		1	PCS
- Recessions in ceiling frame for external electric connections (plug + socket), on short side of unit (2,435 m)		1	PCS
- Single fluorescent lamp, 1x58W, protection IP 65		1	PCS
- Flush mounted light switch LEGRAND(077011), with fuse 10A 2P and cable H05VV-F, IP20		1	PCS
- Flush mounted single socket LEGRAND(077213), 16A 2P, with cable H05VV-F, protection IP20		1	PCS
- Flush mounted double socket LEGRAND(077213), 16A 2P, with cable H05VV-F, protection IP20		2	PCS
- Electric wall heater, convector type, of capacity 2 kW, with electric thermostat, protection IP 20		1	PCS
- Switches and sockets are prepared (in trans-pack) in a way, that they are very easy to assemble		1	PCS
- Rcontainer AS labels, pasted on ceiling frame of modular unit		4	PCS

Remark: the position and exact number of each element, the way of opening etc. is determined on the final drawing.

Any additional information that you might need, do not hesitate to contact us, we will be glad to help you.

We hope that you find our offer interesting and we are looking forward to hearing from you.