

- CONSTRUCTION**
- 4 jack rings for comfortable transportation
  - Metal runners for fork-lift transport and ground ventilation
  - Protective corners offer additional collision protection and stability
  - Best-Point-Technology (joining process, the protective zinc coating is not damaged)

- MATERIAL**
- Galvanized sheet steel S220 GD Z; 1.0241 and S250 GD Z; 1.0242
  - Surface: MB, hot-dip galvanized
  - Trapezoidal sheet thickness: 0.8mm
  - Profile thickness: 1.5mm or 2mm

- OSB FLOOR**
- OSB/3 panel for use in structural applications in humid areas in accordance with EN 300
  - Panel thickness: 18mm
  - Load bearing capacity: 500kg/m<sup>2</sup>
  - Fully PMDI (formaldehyde free) glued, low-emission (E1)
  - Guaranteed pest free (IPPC standard)
  - European building material classification according to EN 13501-1: D - s2, d0

- SAFETY**
- GS-Mark from TÜV North

- CRANE HANDLING**
- MB1: 280kg permissible total weight
  - MB2: 565kg permissible total weight

- SNOW LOAD**
- 2.10kN/m<sup>2</sup>

**SIZE/WEIGHT**

MB		1	2
Width external/internal	(mm)	1100/975	2100/1975
Length external/internal	(mm)	700/575	700/575
Height external/internal	(mm)	1600/1435	1600/1435
Height with castors external/internal	(mm)	1795/1435	1795/1435
Weight	(kg)	100	160

- DOORS**
- MB1: SE (in front face, single door), 950 x 1390mm (clearance dimensions: 958 x 1355mm)
  - MB2: SZ (in front face, double door), 1950 x 1390mm (clearance dimensions: 1958 x 1355mm)
  - With mortise lock (according to DIN 18251-1) and profile cylinder (PZ 25/25), including 3 keys
  - Short plate and door handle pair in aluminium

- DELIVERY**
- Assembled delivery

- ACCESSORIES ONLY FOR THE MB**
- Swivel and fixed castors (Heavy duty wheel with elastic solid rubber tyres and aluminium wheel body, load: 300kg)